



INDIUM CORPORATION OF AMERICA ®\EUROPE®\ASIA-PACIFIC® INDIUM CORPORATION (SUZHOU) ®

This material safety data sheet represents a family grouping of all metal mixes that are blended with the same flux. A table is provided that lists all metal groupings. To better serve all of our customers Indium Corporation has generated one MSDS, for this product, to be used within the United States as well as internationally. Some of the regulatory information contained within may not be applicable to the customer's individual state or country. Unless otherwise stated the health and safety information provided within is applicable to all products.

SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: INDALLOY WITH NC-SMQ80 FLUX VEHICLE

MSDS Number: MSDS-IN 450

Revised Date: 26 FEBRUARY 2010

Product Use: Industrial Use - No-clean solder paste consisting of a flux vehicle blended with a pre-alloyed metal powder. Alloy contained is 83 – 92% in product.

MANUFACTURER:

In America:

The Indium Corporation of America
1676 Lincoln Ave., Utica NY 13502
Information: (315) 853-4900
nswarts@indium.com

EMERGENCY PHONE:

CHEMTREC 24 hrs.
USA: 1 (800) 424-9300
Outside USA: 1 (703) 527-3887

In Europe:

Indium Corporation of Europe
7 Newmarket Ct.
Kingston, Milton Keynes, UK, MK 10 OAG
Information: +44 [0] 1908 580400

In China:

Indium Corporation (Suzhou) Co., Ltd.
No. 428 Xinglong Street
Suzhou Industrial Park
Suchun Industrial Square
Unit No. 14-C
Jiangsu Province, China 215126
Information: (86) 512-6283-4900

In Asia:

Asia-Pacific Operations-Singapore
29 Kian Teck Avenue
Singapore 628908
Information: +65 6268-8678

2. HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY:

⊕Eye ⊕Inhalation ⊕Skin ⊕Ingestion NTP

Carcinogen listed in

IARC OSHA ⊕Not Listed
*See Section 11

POTENTIAL HEALTH EFFECTS:

GHS:



Warning Word: Warning (lead free with rosin)

Warning Word: Danger (lead with rosin)

Eye Contact: Contact with material at room temperature or fume from material at typical re-flow temperatures over 100°C may cause eye irritation.

Ingestion: This product may contain lead alloy powder and organic chemicals. Harmful if swallowed. May cause systematic lead poisoning and burns to the digestive tract. Symptoms of lead poisoning include headache, nausea, abdominal pain, muscle and joint pain and damage to the nervous system, blood system and kidneys.

Inhalation: Vapors or fumes from this material at typical re-flow temperatures over 100°C may cause local irritation to the respiratory system. Rosin exposure may cause occupational asthma.

Skin Contact: May cause mild skin irritation. Rosin may cause dermatitis.

Chronic: LEAD: Prolonged exposure to vapors or fumes at higher temperatures may cause respiratory irritation and systematic lead poisoning. Symptoms of lead poisoning include headache, nausea, abdominal pain, muscle and joint pain and damage to the nervous system, blood system and kidneys.

SILVER: Chronic skin contact or ingestion of silver dust, salts, or fume can result in a condition known as Argyria, a condition with bluish pigmentation of the skin and eyes.

TIN: Has been shown to increase incidence of sarcoma in animal tests.

BISMUTH: May cause kidney damage.

INDIUM: May cause damage to respiratory system.

WARNING: This product contains a chemical known to the State of California to cause cancer and/or birth defects (or other reproductive harm).

NOTE: The Indium Corporation does not recommend, manufacture, market or endorse any of its products for human consumption.

Warning: This product may contain lead. Lead may be harmful to your health. US Federal law prohibits the use of leaded solders in making joints or fittings in any private or public water supply system. Keep out of the reach of children.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Components	% wt	CAS Registry #/EINECS#	PEL mg/m ³	TLV-TWA mg/m ³	TLV-STEL mg/m ³
TIN	*	7440-31-5/231-141-8			
		(US)	2	2	-
		(EU)	-	2	4
		(Canada)	-	2	4
		(Singapore)	2	-	-
LEAD	*	7439-92-1/231-100-4			
		(US)	0.05	0.05	-
		(EU)	-	0.15	-
		(Canada)	0.05	0.05	-
		(Mexico)	0.15	-	-
		(Singapore)	0.15	-	-
		(China)	-	0.05(dust)	-
		0.03(fume)	-		
SILVER	*	7440-22-4/231-131-3			
		(US)	0.01	0.1	-
		(EU)	-	0.1	-
		(Canada)	-	0.1	0.3
		(Mexico)	0.1	-	-
(Singapore)	0.1	-	-		
INDIUM	*	7440-74-8/231-180-0			
		(US)	0.1	0.1	-
		(EU)	-	0.1	0.3

		(Canada)	-	0.1	0.3
		(Mexico)	0.1	-	0.3
		(Singapore)	0.1	-	-
		(China)	-	0.1	0.3
BISMUTH	*	7440-69-9/231-177-4	N.E.	N.E.	N.E.
ROSIN	4.0 - 5.0	8052-10-6	N.E.	N.E.	N.E.
		(EU)	0.05	N.E.	0.15 (sensitiser)
POLYGLYCOL ETHER	2.8 – 6.0	9038-95-3	N.E.	N.E.	N.E.
NON HAZARDOUS ACTIVATORS	1.2 - 7.0	-	N.E.	N.E.	N.E.
PRODUCT DOES NOT CONTAIN ANY REPORTABLE EU SUBSTANCES OF VERY HIGH CONCERN (SVHC)					
Symbol: X _n		Risk Phrases: R20/21/22, R36/37/38, R42/43			
N.E. = Not established		EU = European Union Occupational Exposure Limits			* See Alloy Table

ALLOY TABLE**% Metal mix with flux – ALLOY 83-92%**

Indalloy (metal)	RoHS Compliance*	%TIN Sn	%SILVER Ag	%LEAD Pb	%BISMUTH Bi	%INDIUM In
1 (50In/50Sn)	Yes	41.5-46.0	-	-	-	41.5-46.0
1E (52In/48Sn)	Yes	39.8-44.2	-	-	-	43.2-47.8
2 (80In/15Pb/5Ag)	No	-	4.2-4.6	12.5-13.8	-	66.4-73.6
3 (90In/10Ag)	Yes	-	8.3-9.2	-	-	74.7-82.8
4 (100In)	Yes	-	-	-	-	83.0-92.0
5 (37.5Pb/37.5Sn/25In)	No	31.1-34.5	-	31.1-34.5	-	20.8-23.0
7 (50In/50Pb)	No	-	-	41.5-46.0	-	41.5-46.0
9 (70Sn/18Pb/12In)	No	58.1-64.4	-	14.9-16.6	-	10.0-11.0
10 (75Pb/25In)	No	-	-	62.3-69.0	-	20.8-23.0
11 (95Pb/5In)	Yes	-	-	78.9-87.4	-	4.2-4.6
40	No	15.8-17.5	-	25.7-28.5	41.5-46.0	-

(50Bi/31Pb/19Sn)						
42 (46Bi/34Sn/20Pb)	No	28.0-31.3	-	17.0-18.4	38.0-42.3	-
53 (67Bi/33In)	Yes	-	-	-	54.9-61.6	27.1-30.4
70 (40In/40Sn/20Pb)	No	32.8-36.8	-	16.4-18.4	-	32.8-36.8
97 (43Sn/43Pb/14Bi)	No	36.7-39.6	-	36.7-39.6	11.6-12.9	-
150 (81Pb/19In)	No	-	-	67.2-74.5	-	15.8-17.5
164 (92.5Pb/5In/2.5Ag)	Yes	-	2.1-2.3	76.8-85.1	-	4.2-4.6
174 (57Bi/26In/17Sn)	Yes	14.1-15.6	-	-	47.3-52.4	21.6-23.9
Indalloy (metal)	RoHS Compliance*	%TIN Sn	%SILVER Ag	%LEAD Pb	%BISMUTH Bi	%INDIUM In
204 (70In/30Pb)	No	-	-	24.9-27.6	-	58.1-64.4
205 (60In/40Pb)	no	-	-	33.2-36.8	-	49.8-55.2
206 (60Pb/40In)	No	-	-	49.8-55.2	-	33.2-36.8
227 (77.2Sn/20In/2.8Ag)	Yes	64.1-71.0	2.3-2.6	-	-	16.6-18.4
230 (54Sn/26Pb/20In)	No	44.8-49.7	-	21.6-23.9	-	16.6-18.4
249 (91.8Sn/4.8Bi/3.4Ag)	Yes	76.2-84.5	2.8-3.1	-	4.0-4.4	-
254 (86.9Sn/10In/3.1Ag)	Yes	72.1-79.9	2.6-2.9	-	-	8.3-9.2
281 (58Bi/42Sn)	Yes	34.9-38.6	-	-	48.1-53.4	-
290 (97In/3Ag)	Yes	-	2.5-2.8	-	-	80.5-89.2
NON STANDARD ALLOY (88Sn/10In/2Ag)	Yes	73-81	1.7-1.8	-	-	8.3-9.2

*RoHS = Restriction of Hazardous Substances (review applicable exemption)

<http://pbfree.com>

4. FIRST AID MEASURES

- Eye Contact:** Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Seek medical attention if irritation persists.
- Ingestion:** If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give anything by mouth to an unconscious person. Seek medical attention immediately.
- Inhalation:** Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel. Seek immediate medical attention.
- Skin Contact:** Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before reuse. If irritation persists, obtain medical attention.

5. FIRE FIGHTING MEASURES

- Flash Point:** Not flammable rated >200F (>93C)
- Auto-ignition Temperature:** Not established.
- Flammable Limits:** NA
- Extinguishing Media:** Use extinguishers appropriate for the surrounding fire conditions.
- Special Fire Fighting Procedures:** Firefighters must wear NIOSH approved self-contained breathing apparatus and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

- Spill or Leak Procedures:** Using a spatula, scoop up paste and place in a plastic or glass jar and tightly cap. Remove traces of paste residue using cloth rags or paper towels moistened with ethyl or isopropyl alcohol. Dispose of contaminated cloth rags or paper towels following all Federal, State and Local regulations.

7. HANDLING AND STORAGE

- Handling Precautions:** Keep containers tightly closed when not in use. Use care to avoid spills. Use only with production equipment specifically designed for use with solder paste. Wear appropriate personal protective equipment when working or handling solder paste. Always thoroughly wash your hands after handling this product. DO NOT touch or rub eyes until hands are washed.
- Storage Precautions:** Store product in tightly capped original containers in a cool, dry area. Refer to product label for specific storage temperature requirements. Rotate stock to ensure use before expiration date on the label.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Use only with production equipment (stencil printers and re-flow furnaces) with adequate ventilation and other safety features specifically designed for use with solder paste. Control concentration of all components so that the exposure levels are not exceeded.

Personal protection:

Eyes: Chemical safety glasses/goggles.

Respirator: An authority approved or compliant marked air-purifying respirator with a fume/organic chemical cartridge is recommended under certain circumstances (i.e. when re-flowing manually on a plate instead of a ventilated re-flow furnace) where airborne concentrations are expected to be elevated or exceed exposure limits.

Skin: Compatible chemical resistant gloves.

Other: Lab coat, eye-wash fountain in work area. Avoid the use of contact lenses in high fume areas.

Work/Hygienic Practices: Maintain good housekeeping. Clean up spills immediately. DO NOT allow rags or paper towels contaminated with solder paste to accumulate in the work area. Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area. Wash hands thoroughly with soap and water immediately upon leaving the work area.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Grey colored paste.

Boiling Point: Not applicable.

Odor: Mild characteristic odor.

Melting Point: (25-45C above alloy melting temp temperature)

Specific Gravity: Not applicable.

pH: Not applicable

Vapor Pressure: Not applicable.

Solubility in Water: Insoluble (paste)

Vapor Density: (air=1) Not applicable.

10. STABILITY AND REACTIVITY

General: Stable.

Conditions to Avoid: Not established.

Incompatible Materials: Avoid contact with acids, bases or oxidizing agents.

Hazardous Decomposition / Combustion: Harmful organic fumes and toxic oxide fumes may form at elevated temperatures.

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Carcinogenicity: NTP: No

OSHA: No 29CFR1910.1025

IARC: Yes Lead and lead compounds are listed as possible carcinogens.

Solder paste is not classified under any agency {NTP/OSHA/IARC}. Proprietary ingredients are not listed as carcinogens.

Other: Chronic Toxicity: Prolonged or repeated exposure to rosin flux fume may cause workers to develop occupational asthma. Lead can cause potential harm to the developing fetus.

12. ECOLOGICAL INFORMATION

This section is subject to future development. Product not tested.

13. DISPOSAL CONSIDERATION

Waste Disposal Method: Scrap metal alloy usually has value. Contact a commercial reclaimer for recycling. Otherwise, dispose of in accordance with all Federal, State and Local environmental regulations. In Europe follow the Special Waste Regulations.

14. TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements. Not regulated under US DOT (United States Department of Transportation). Not hazardous under UN shipping regulations.

North American Emergency Guide Book – Not classified

15. REGULATORY INFORMATION

The information in this Material Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

The information in this Material Safety Data Sheet meets the requirements of the EU under Chemicals (Hazard Information and Packaging for Supply) Regulations 1994 (CHIP 2) Regulation 6.

This product has been classified in accordance with the hazard criteria of the Commission Directive 91/155/EEC and EH40.

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).

WHMIS: D2B –Materials Causing Other Toxic Effects (irritant or sensitizer)

WHMIS: D2A-Materials Causing Other Toxic Effects-Very Toxic Material (Chronic) (lead)



This product has been classified in accordance with the Mexican regulations: NOM-018-STPS-2000 and NOM – 010-STPS-1999.

This product has been classified in accordance with the guidelines set by the Dept of Industrial Health of the Republic of Singapore.

California PROP 65 (Safe Drinking Water Standard):

This product contains a chemical known to the State of California to cause cancer and/or birth defects (or other reproductive harm). (Lead CAS# 7439-92-1)

SARA 313 Listing - 40 CFR 372.65

Lead CAS# 7439-92-1 Silver CAS# 7440-22-4

EPA Genetic Toxicology Program – Lead CAS# 7439-92-1

All ingredients are listed on the EPA TSCA Inventory.

All ingredients are listed on the Canadian Domestic Substance List.

EC Classification, Packaging and Labeling Requirements:

Symbol and Hazard Classification of Product

X_n

Risk Phrases:

- R20/21/22 Harmful by inhalation, in contact with skin and if swallowed
- R36/37/38 Irritating to eyes, respiratory system and skin
- R42/43 May cause sensitization by inhalation and skin contact
- R33 Danger of cumulative effects (lead)
- R40 Limited evidence of carcinogenic effect (lead)
- R48 Danger of serious damage to health by prolonged exposure (lead)
- R61 May cause harm to the unborn child (lead)

Safety Phrases:

- S20/21 When using do not eat, drink or smoke
- S22 Do not breathe dust
- S23 Do not breathe fumes
- S24/25 Avoid contact with skin and eyes
- S27 Take off immediately all contaminated clothing
- S28 After contact with skin wash immediately with plenty of soap and water
- S36/37/39 Wear suitable protective clothing, gloves and eye/face protection
- S62 If swallowed, do not induce vomiting seek medical advice immediately and show container or label
- S7 Keep container tightly closed

16. OTHER INFORMATION

HMIS Hazard Rating: **Health:** 2
 Fire: 1
 Reactivity: 0

Revised Date: 26 FEBRUARY 2010

Prepared by: Nancy Swarts, Indium Corporation of America

Approved by: Nancy Swarts, Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.