INDIUM CORPORATION®

PRODUCT DATA SHEET

Gallium Trichloride, Anhydrous (GaCl₃)

| Synonyms | Gallium Chloride, Gallium (III) Chloride | |
|-----------------------------|--|--|
| CAS Number | 13450-90-3 | |
| EC (EINECS/ELINCS) Number | 236-610-0 | |
| RTECS | LW9100000 | |
| Purity | 99.5 to 99.999% GaCl ₃ | |
| Appearance | Clear or White, Needle-shaped Crystals; Deliquescent; Fumes in Air | |
| Form | Solid Polycrystalline or Free-Flowing Granule | |
| Formula Weight | 176.08 g/mol | |
| Theoretical Gallium Content | 39.596% | |
| Density: | | |
| Solid | 2.47 g/cm ³ | |
| Liquid | 2.05 g/cm ³ at mp | |
| Melting Point | 77.9°C | |
| Boiling Point | 201.3°C at 760 torr | |
| Vapor Pressure | 48°C = 1 torr | |
| | 78°C = 10 torr | |
| Solubility | Soluble in Water, Ammonia, Benzene, Ethers, Carbon Disulfide, Carbon Tetrachloride | |

| Impurities (99.999%) | Typical (ppm) | Maximum (ppm) |
|-----------------------|---------------|---------------|
| Aluminum (Al) | <1 | 5.0 |
| Copper (Cu) | <1 | 3.0 |
| Iron (Fe) | <1 | 4.0 |
| Germanium (Ge) | <1 | 5.0 |
| Indium (In) | <1 | 5.0 |
| Sodium (Na) | <1 | 5.0 |
| Nickel (Ni) | <1 | 1.0 |
| Lead (Pb) | <1 | 5.0 |
| Tin (Sn) | <1 | 5.0 |
| Zinc (Zn) | <1 | 5.0 |
| Total Combined Metals | < 3 | 10.0 |

All information is for reference only. Not to be used as incoming product specifications.

Packaging

Glass Bottle, screw closure: 100g, 500g, and 1kg Teflon PFA, screw closure: 100g, 500g, and 1kg

Material is shipped in UN/DOT, IATA, and IMDG compliant packaging.

Storage and Shelf Life

Gallium trichloride is highly deliquescent and the solid crystals will liquefy quickly in humid environments. The container should contain a desiccant and the container kept tightly sealed. **Gallium trichloride** has a shelf life of 6 months due to the deliquescent nature of the chemical.

This product data sheet is provided for general information only. It is not intended, and shall not be construed, to warrant or guarantee the performance of the products described which are sold subject exclusively to written warranties and limitations thereon included in product packaging and invoices. All Indium Corporation's products and solutions are designed to be commercially available unless specifically stated otherwise.

www.indium.com askus@indium.com

ASIA: Singapore, Cheongju: +65 6268 8678
CHINA: Suzhou, Shenzhen: +86 (0)512 628 34900
EUROPE: Milton Keynes, Torino: +44 (0) 1908 580400
USA: Utica, Clinton, Chicago, Rome: +1 315 853 4900



ISO 9001 REGISTERED