INDIUM TRIIODIDE InI₃

General Information

Molecular Weight: 495.53 % of Indium: 23.17% Specific Gravity: 4.69 gr/cc Melting Point: 210°C **Boiling Point:** Sublimes

Crystalline Form: Carmine red or yellow crystals

Isomorphous with: AlCl₃, YCl₃

Coordination Number: 6

Solubility in Water: 92.91 grams/100 grams of solution

Density 3.4 gr/cc

Safety Data: Material Safety Data Sheet (MSDS)

Available on request and shipped

with product.

Standard Packaging

Quantity*	Container	
3.5 kg	l gallon Nalgene	
2.0 kg	¹ /2 gallon Nalgene	
1.0 kg	l liter Nalgene	
500 g	¹ /2 liter Nalgene	
100-200 g	Plastic Jars	

*All package sizes contain suitable dessicant. Packaging in other sizes or in glass may be available upon request. See below for available

Grades Available vs. Typical Analysis PPM WT

Element	99.9%	99.99%	99.999%
Aluminum	1-10	1-10	0.1 - 1
Antimony	NF	NF	NF
Arsenic	NF	NF	NF
Cadmium	50-100	5-10	1
Chromium	NF	NF	NF
Copper	5-10	1–2	0.5
Iron	10-20	1–2	0.5
Lead	200-300	10–30	2
Molybdenum	NF	NF	NF
Nickel	1–5	10–20	0.5
Thallium	100-300	10–20	1
Tin	50-100	10–20	2
Vanadium	NF	NF	NF
Silicon	1-10	1-10	0.1 - 1
Magnesium	1-10	1-10	0.1 - 1

Note: Specific impurities within a grade can sometimes be more tightly specified.

NF = Not Found



INDIUM CORPORATION OF AMERICA®

All statements, technical information and recommendations contained herein are based on tests, or All statements, technical information and recommendations contained nerein are based on tests, other information, available to us which we believe to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties express or implied, including warranties of merchantability and fitness. Our only obligation shall be to replace such quantities of the product as is proved to be defective provided that a claim is submitted to us within 60 days from the date of shipment. We shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. It shall be solely the purchaser's obligation to determine the suitability of the product for his intended use and the

purchaser assumes all risk and liability whatsoever in connection therewith.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by an authorized representative or seller.

Since we have no means of controlling the final use of the product by the consumer or purchaser it is the responsibility of the immediate purchaser and any intermediate seller or sellers to inform the user of the purposes for which the product may be fit and suitable and of the properties of the product, including any precautionary measures which must be taken in order to insure the safety of the user and of other third persons and property.

CORPORATE HEADQUARTERS-USA: 1676 Lincoln Avenue, Utica, NY, USA 13502 • askus@indium.com • 315-853-4900 or 800-4 INDIUM • FAX 315-853-1000 or 800-221-5759 ASIA-PACIFIC OPERATIONS-SINGAPORE: 29 Kian Teck Avenue, Singapore 628908 • asiapac@indium.com • +65 268-8678 • FAX +65 268-5646 INDIUM CORPORATION OF EUROPE-UK: 7 Newmarket Court, Kingston, Milton Keynes MK10 0AG UK • europe@indium.com • +44 (0)1908 580400 • FAX +44 (0)1908 580411 INDIUM CORPORATION OF AMERICA-ITALY: Via Principe Tommaso, 55 • I-10125 • Turin Italy • +39-011-655331 • FAX +39-011-655490