

Introduction

TACFlux® 032 is a rework flux for Pb-free alloys in an air or inert gas reflow atmosphere. **TACFlux® 032** provides excellent wetting in air or nitrogen atmospheres.

Properties

Industry Standard Test Results and Classification			
Flux Classification	ORH1	Viscosity (C&P)* Typical	11kcps
Based on the testing required by ANSI/IPC J-Standard-004B		*Brookfield Cone & Plate	
Tack Typical	150g	(CP51, 5rpm, 5 minutes, 25°C)	

All information is for reference only.

Not to be used as incoming product specifications.

Additional Test Results			
Test	Result		
Appearance	Light Yellow-Amber		
Maximum Reflow Temperature	350°C		
Reflow Atmosphere	Air or Nitrogen		
Shelf Life	One year @ 0–30°C		
Storage Condition	Stored @ 0–30°C (tip down for syringe or cartridge)		

All information is for reference only.

Not to be used as incoming product specifications.

Packaging

TACFlux® 032 is available in 10 and 30cc syringes or 100g jars; however, other packaging can be provided to meet specific requirements.

Cleaning

TACFlux®032 is designed for DI water-wash applications.

Storage

TACFlux® 032 syringes and cartridges should be stored tip down at 0–30°C. If refrigerated, **TACFlux® 032** should be allowed to stand for at least 4 hours at room temperature before using.

Technical Support

Indium Corporation's internationally experienced engineers provide in-depth technical assistance to our customers. Thoroughly knowledgeable in all facets of Material Science as it applies to the electronics and semiconductor sectors, Technical Support Engineers provide expert advice in solder properties, alloy compatibility and selection of solder preforms, wire, ribbon, and paste. Indium Corporation Technical Support Engineers provide rapid response to all technical inquiries.

Safety Data Sheets

The SDS for this product can be found online at http://www.indium.com/sds

This product data sheet is provided for general information only. It is not intended, and shall not be construed, to warrant or guarantee the performance of the products described which are sold subject exclusively to written warranties and limitations thereon included in product packaging and invoices. All Indium Corporation's products and solutions are designed to be commercially available unless specifically stated otherwise.

All of Indium Corporation's solder paste and preform manufacturing facilities are IATF 16949:2016 certified. Indium Corporation is an ISO 9001:2015 registered company.

From One Engineer To Another[®]

Contact our engineers: askus@indium.com Learn more: www.indium.com

ASIA +65 6268 8678 • CHINA +86 (0) 512 628 34900 • EUROPE +44 (0) 1908 580400 • USA +1 315 853 4900



Form No. 99626 (A4) R1

©2020 Indium Corporation

