# PRODUCT DATA SHEET CF100 PEACH Compliant I

## **REACH-Compliant Liquid Flux**

#### Introduction

**CF100** is a heat-stabilized rosin flux designed for soldering with preforms or wire. It is formulated for use with a wide range of temperatures and metallizations, and is free of materials listed in the REACH SVHC list (Q2, 2015).

**CF100** is a no-clean, mildly activated flux. It is compatible with Pb-free alloys, as well as with high-Pb and SnPb alloys.

#### **Cleaning**

**CF100** is a no-clean flux. Removal of post-reflow flux residue is usually not necessary. If cleaning is desired, commercially available flux residue removers can be used.

#### **Packaging**

Standard packaging for **CF100** is 1 U.S. pint (0.473 liter) and 1 U.S. gallon (3.785 liters).

Properties	CF100 Flux	Test Method
Flux Type	ROL0	J-STD-004
Application Technique	Spray	
Specific Gravity	0.9	
Typical Viscosity	13-17cSt	Brookfield viscometer or Zahn Cup
SIR Testing	Pass	J-STD-004
Typical Acid Value	78-98mg KOH/g	Titration
Typical Tack Strength	Below detection limit	J-STD-005
Shelf Life at 18–30°C	1 year	Viscosity change/ microscope examination
Typical Post-Reflow Residue Weight	<10%	TGA data post-reflow residue

All information is for reference only.

Not to be used as incoming product specifications.

#### **Storage and Handling**

The shelf life of **CF100** is 1 year when stored at 18–30°C. Flux should be allowed to reach ambient temperature prior to use. Containers should be labeled with date and time of opening.

#### **Technical Support**

Indium Corporation sets the industry standard in providing rapid response, onsite technical support for our customers worldwide. Indium Corporation's team of Technical Support Engineers can provide expertise in all aspects of Materials Science and Semiconductor Packaging process applications.

#### **Safety Data Sheets**

The SDS for this product is available by contacting askus@indium.com

#### **Recommended Application Notes**

- Flux and Solder Compatibility (Form No. 97751)
- Common Elements (Form No. 98557)
- Pb-Free Solder FAQs (Form No. 97758)
- Practical Suggestions for Preform Design (Form No. 97763)

#### **Other Recommended Products**

- Solder preforms
- · Solder wire
- · Solder research kits

This product data sheet is provided for general information only. It is not intended, and shall not be construed, to warrant or guarantee the performance of the products described which are sold subject exclusively to written warranties and limitations thereon included in product packaging and invoices. All Indium Corporation's products and solutions are designed to be commercially available unless specifically stated otherwise.

All of Indium Corporation's solder paste and preform manufacturing facilities are IATF 16949:2016 certified. Indium Corporation is an ISO 9001:2015 registered company.

### From One Engineer To Another

Contact our engineers: askus@indium.com

Learn more: www.indium.com

Form No. 99689 R3

